

1. Unique identification code of the product-type:
Code 27 – Residential space heating appliances fired by wood pellets (BDS EN 16510-2-6:2022).
BIJOU II 10
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Serial number- see the product label
3. Intended use or uses of the construction product, in accordance with the applicable harmonised specification, as foreseen by the manufacturer:
Freestanding pellet stove with a water heating function, designed for operation with the door closed and featuring an automatic fuel feed system. Intended for heating residential spaces.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with the requirements of Article 11, paragraph 5:
NIKO THERM ENGINEERING Ltd
20 Maritsa St., 5100 Gorna Oryahovitsa, Republic of Bulgaria; email:office@niko-therm.com
5. System or systems of assessment and verification of constancy of performance of the construction product, as set out in Annex V: **System 3**
6. Declaration of performance for a construction product covered by a harmonised standard:
Control 94 Ltd
5100 Gorna Oryahovitsa, Republic of Bulgaria, 2 Mladost St.; Identification number NB1879
Test Report № 1879-ITT-0094/15.06.2026

7. Declared performance

Harmonized technical specification	БДС EN 16510-2-6:2022	
	Operational performance indicators	
Fire Safety		
Reaction to fire	A1	
Minimum distances to combustible materials, mm	Rear (dR) – 300, sides (dS) – 300, top (dC) – 400, front (dP) – 500, floor in front of the appliance (dF) – 300, sides in front of the appliance (dL) – 300, under the appliance (dB) – 0	
Risk of ignition in the event of fuel spillage	Verified	
Surface temperature of the working parts	Verified	
Electrical safety	Verified	
Cleaning	Verified	
Maximum water operating pressure	2 bar	
Mechanical resistance (support for the chimney/flue)	Not applicable	
	Nominal heat output	Reduced heat output
CO emissions in combustion products at 13% O ₂	66 mg/Nm ³	70 mg/Nm ³
Flue gas temperature	85 °C	75 °C
Thermal power output	10.22 kW	5.82 kW
Water heater capacity	7.70 kW	3.8 kW
Spatial heat flux	2.52 kW	1.98 kW
Efficiency	95.1%	94.9%
Emissions in combustion products at 13% O ₂		
PM (mg/m ³)	11.2 mg/Nm ³	14.5 mg/Nm ³
OGC (mg/m ³)	6 mg/Nm ³	10 mg/Nm ³
NO _x	89 mg/Nm ³	58 mg/Nm ³

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer:
08.07.2026:

Gorna Oryahovitsa

Manager: 
(Eng. Nikolay Tsvetanov)

1. Unique identification code of the product-type:
Code 27 – Residential space heating appliances fired by wood pellets (BDS EN 16510-2-6:2022).
BIJOU II 16
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Serial number- see the product label
3. Intended use or uses of the construction product, in accordance with the applicable harmonised specification, as foreseen by the manufacturer:
Freestanding pellet stove with a water heating function, designed for operation with the door closed and featuring an automatic fuel feed system. Intended for heating residential spaces.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with the requirements of Article 11, paragraph 5:
NIKO THERM ENGINEERING Ltd
20 Maritsa St., 5100 Gorna Oryahovitsa, Republic of Bulgaria; email:office@niko-therm.com
5. System or systems of assessment and verification of constancy of performance of the construction product, as set out in Annex V: **System 3**
6. Declaration of performance for a construction product covered by a harmonised standard:
Control 94 Ltd
5100 Gorna Oryahovitsa, Republic of Bulgaria, 2 Mladost St.; Identification number NB1879
Test Report № 1879-ITT-0094/15.06.2026

7. Declared performance

Harmonized technical specification	БДС EN 16510-2-6:2022	
	Operational performance indicators	
Fire Safety		
Reaction to fire	A1	
Minimum distances to combustible materials, mm	Rear (dR) – 300, sides (dS) – 300, top (dC) – 400, front (dP) – 500, floor in front of the appliance (dF) – 300, sides in front of the appliance (dL) – 300, under the appliance (dB) – 0	
Risk of ignition in the event of fuel spillage	Verified	
Surface temperature of the working parts	Verified	
Electrical safety	Verified	
Cleaning	Verified	
Maximum water operating pressure	2 bar	
Mechanical resistance (support for the chimney/flue)	Not applicable	
	Nominal heat output	Reduced heat output
CO emissions in combustion products at 13% O ₂	56 mg/Nm ³	63 mg/Nm ³
Flue gas temperature	91 °C	66 °C
Thermal power output	15,17 kW	7,38 kW
Water heater capacity	11.5 kW	5.27 kW
Spatial heat flux	3.67 kW	2.11 kW
Efficiency	95.2%	95,1%
Emissions in combustion products at 13% O ₂		
PM (mg/m ³)	12.4 mg/Nm ³	11.5 mg/Nm ³
OGC (mg/m ³)	5 mg/Nm ³	10 mg/Nm ³
NO _x	101 mg/Nm ³	91 mg/Nm ³

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer:
08.07.2026:

Gorna Oryahovitsa

Manager: 
(Eng. Nikolay Tsvetanov)

1. Unique identification code of the product-type:

Code 27 – Residential space heating appliances fired by wood pellets (BDS EN 16510-2-6:2022).

BIJOU II 25

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Serial number- see the product label

3. Intended use or uses of the construction product, in accordance with the applicable harmonised specification, as foreseen by the manufacturer:

Freestanding pellet stove with a water heating function, designed for operation with the door closed and featuring an automatic fuel feed system. Intended for heating residential spaces.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer in accordance with the requirements of Article 11, paragraph 5:

NIKO THERM ENGINEERING Ltd
20 Maritsa St., 5100 Gorna Oryahovitsa, Republic of Bulgaria; email:office@niko-therm.com

5. System or systems of assessment and verification of constancy of performance of the construction product, as set out in Annex V:
- System 3**

6. Declaration of performance for a construction product covered by a harmonised standard:

Control 94 Ltd
5100 Gorna Oryahovitsa, Republic of Bulgaria, 2 Mladost St.; Identification number NB1879
Test Report № 1879-ITT-0094/15.06.2026

7. Declared performance

Harmonized technical specification	БДС EN 16510-2-6:2022	
	Operational performance indicators	
Fire Safety		
Reaction to fire	A1	
Minimum distances to combustible materials, mm	Rear (dR) – 300, sides (dS) – 300, top (dC) – 400, front (dP) – 500, floor in front of the appliance (dF) – 300, sides in front of the appliance (dL) – 300, under the appliance (dB) – 0	
Risk of ignition in the event of fuel spillage	Verified	
Surface temperature of the working parts	Verified	
Electrical safety	Verified	
Cleaning	Verified	
Maximum water operating pressure	2 bar	
Mechanical resistance (support for the chimney/flue)	Not applicable	
	Nominal heat output	Reduced heat output
CO emissions in combustion products at 13% O ₂	56 mg/Nm ³	60 mg/Nm ³
Flue gas temperature	101 °C	77 °C
Thermal power output	22.5 kW	10.5 kW
Water heater capacity	17.6 kW	6.4 kW
Spatial heat flux	4.9 kW	4.1 kW
Efficiency	93.2%	92.4%
Emissions in combustion products at 13% O ₂		
PM (mg/m ³)	12.4 mg/Nm ³	11.5 mg/Nm ³
OGC (mg/m ³)	8 mg/Nm ³	12 mg/Nm ³
NOx	99 mg/Nm ³	96 mg/Nm ³

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer:

08.07.2026:

Gorna Oryahovitsa

Manager:
(Eng. Nikolay Tsvetanov)
